

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 September 2006 (14.09.2006)

PCT

(10) International Publication Number
WO 2006/094426 A1

(51) International Patent Classification:
H04L 29/06 (2006.01)

(21) International Application Number:
PCT/CN2005/000263

(22) International Filing Date: 5 March 2005 (05.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **INTEL CORPORATION** [US/US]; 2200 Mission College Blvd., Santa Clara, CA 95052 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WANG, Zhi** [CN/CN]; N430, Apt 402, Dongyuan Sicun, Shanghai 200000 (CN). **JIAN, Rui** [CN/CN]; N5 Apt 301, Lane 1664, Xie Tu Rd., Shanghai 200032 (CN). **DENG, Ying'an**; 9#202, Lane 560, Yu Ping South Rd., Shanghai 200000 (CN). **SUN, Yuanhao**; N26 Apt 402, Lane 26, Gu Jing Road, Shanghai 200336 (CN). **SONG, Caidong**; N181 Apt. 403 Tianshan Wu Cun, Maotai Road, Changning District, Shanghai 200000 (CN).

(74) Agent: **CHINA PATENT AGENT (H.K.) LTD.**; 22/F, Great Eagle Centre, 23 Harbour Road, Wanchai, Hong Kong (CN).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: SERVER SIDE TFTP FLOW CONTROL



(57) Abstract: Methods and apparatuses for server side flow control. Receive a request from a first client device to multicast a file as a plurality of packets of data from a server device to multiple client device; transmit the plurality of packets of data from a server to the multiple client devices using a multicast trivial file transfer protocol (TFTP); and apply, by the server, one or more flow control techniques not defined by the multicast TFTP.



WO 2006/094426 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

SERVER SIDE TFTP FLOW CONTROL

TECHNICAL FIELD

[0001] Embodiments of the invention relate to file transfer. More particularly, embodiments of the invention relate to server side flow control for the Trivial File Transfer Protocol (TFTP).

BACKGROUND

[0002] Trivial File Transfer Protocol (TFTP) is a simple file transfer protocol that operates in a lock step fashion. That is, each packet is acknowledged by a receiving client and the server does not transmit the subsequent packet until the acknowledgement is received for the previous packet. One embodiment of TFTP is described formally in Request for Comments (RFC) 1350, Rev. 2, published July 1992. Because of simplicity, TFTP is used in pre-boot environments and/or embedded systems. Typical usage may include download of an operating system loader or upgrading of a system image or BIOS.

[0003] However, as file sizes increase and/or packets are lost during transmission, the performance provided by TFTP may be unacceptable because large file sizes and repeated transmission of packets may overload network infrastructure components. Thus, TFTP may be insufficient for more complex file download conditions.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the invention are illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings in which like reference numerals refer to similar elements.

Figure 1 is a block diagram of a network that may connect a server to multiple clients.

Figure 2 is a flow chart of one embodiment of a main flow of operation of a server device that may provide server side flow control of a TFTP and/or multicast TFTP session.

Figure 3 is a flow chart of operation of one embodiment of an upload request handler executed by a server device that may provide server side flow control of a TFTP and/or multicast TFTP session.

Figure 4 is a flow chart of operation of one embodiment of a unicast download request handler executed by a server device that may provide server side flow control of a TFTP and/or multicast TFTP session.

Figure 5 is a flow chart of operation of one embodiment of a multicast download request handler executed by a server device that may provide server side flow control of a TFTP and/or multicast TFTP session.

Figure 6 is a block diagram of one embodiment of an electronic system.

DETAILED DESCRIPTION

[0004] In the following description, numerous specific details are set forth. However, embodiments of the invention may be practiced without these specific details. In other instances, well-known circuits, structures and techniques have not been shown in detail in order not to obscure the understanding of this description.

[0005] **Figure 1** is a block diagram of a network that may connect a server to multiple clients. Server 100 may be coupled with any number of clients (e.g., 140, 150, 160) via network 120, which operate according to any network communication protocol known in the art.

[0006] Currently the Trivial File Transfer Protocol (TFTP) may be used to transfer files between devices. In general, TFTP is a transfer protocol that is simpler to use than the File Transfer Protocol (FTP), but provides less functionality. For example, TFTP does not support user authentication or directory visibility. TFTP uses the User Datagram Protocol (UDP) rather than the Transmission Control Protocol (TCP). One embodiment of TFTP is described formally in Request for Comments (RFC) 1350, Rev. 2, published July 1992.

[0007] TFTP has been expanded to include a multicast option as described in RFC 2090, published February 1997. Multicast TFTP classifies client devices as active clients or passive clients. There is only one active client at a time. The active client communicates with a server to download data using a stop-and-wait ARQ flow and error control technique to a negotiated group address. Passive

clients snoop on the download to the active client and capture data destined for the group address. When the active client finishes downloading the data, a passive client is selected as a new active client.

[0008] In one embodiment, one client, for example, client 160, may operate as an active client as defined by the multicast TFTP to request download of a file from server 100. Any number of additional clients, for example, clients 140 and 150, may operate as passive clients as defined by the multicast TFTP to receive packets corresponding to the file requested by the active client. Upon completion of the download by the active client one of the passive clients may become a new active client to download missing packets.

[0009] In the description herein, the term “packet” refers to any block of data, which can be, for example, a predefined, fixed length or variable in length. In one embodiment, a packet is defined by the multicast TFTP definition. In alternate embodiments, other packet sizes may be used.

[0010] Multicast TFTP does not define techniques for server-side flow control. In one embodiment, a multicast TFTP session may be managed by server 100 using one or more flow control techniques described herein. The TFTP standard relies on a lock-step transfer model in which every packet is acknowledged by the client device before the server transmits a subsequent packet. This does not allow the transfer rate to be controlled by the server device.

[0011] In one embodiment a passive client may join the multicast group during file download. For these passive clients, packets transmitted prior to

joining the multicast group may be received when the missing packets are retransmitted to a new active client.

[0012] Figure 2 is a flow chart of one embodiment of a main flow of operation of a server device that may provide server side flow control of a TFTP and/or multicast TFTP session. The server may monitor a designated port to detect packets that may carry requests for download of a file, 200. In one embodiment, the server device may execute a multi-threaded application that includes one thread that monitors the designated port. The designated port may be, for example, UDP port 69 as defined by the TFTP standard; however, other ports may also be used.

[0013] When a packet is received via the designated port, the application may analyze the packet to determine whether the packet includes a request from a client device, 210. In response to a request from a client device, the application may call the appropriate request handler, 220. After calling the request handler, the application may return to monitoring the designated port. In one embodiment, at least the following three request handlers are implemented by the application and/or by another application executed by the server device: an upload request handler (Fig 3), a unicast download request handler (Fig. 4), and a multicast download request handler (Fig. 5). In alternate embodiments, additional and/or different request handlers may be supported.

[0014] Figure 3 is a flow chart of operation of one embodiment of an upload request handler executed by a server device that may provide server side flow

control of a TFTP and/or multicast TFTP session. In response to being invoked, the upload handler may determine whether the corresponding request is a duplicated request, 300. If the request is a duplicate request, the upload handler may return because the requested upload has been processed.

[0015] If the request is not a duplicate, 300, the upload request handler may determine whether the host server has satisfactory resources available to process the request, 310. If the server does not have satisfactory resources available, the upload handler may cause an error packet to be sent to the requesting client device, 330. If the server does have satisfactory resources available, the upload handler may save session information that may be used, for example, by other request handlers, and the upload request handler may create a thread to service the request, 320. Server side flow control techniques that may be used in servicing the upload request are described in greater detail below.

[0016] **Figure 4** is a flow chart of operation of one embodiment of a unicast download request handler executed by a server device that may provide server side flow control of a TFTP and/or multicast TFTP session. In response to being invoked, the unicast download handler may determine whether the corresponding request is a duplicated request, 400. If the request is a duplicate request, the unicast download handler may return because the requested download has been processed.

[0017] If the request is not a duplicate, 400, the unicast download request handler may determine whether the host server has satisfactory resources

available to process the request, 410. If the server does not have satisfactory resources available, the unicast download handler may cause an error packet to be sent to the requesting client device, 430. If the server does have satisfactory resources available, the unicast download handler may save session information that may be used, for example, by other request handlers, and the unicast download request handler may create a thread to service the request, 420. Server side flow control techniques that may be used in servicing the unicast download request are described in greater detail below.

[0018] Figure 5 is a flow chart of operation of one embodiment of a multicast download request handler executed by a server device that may provide server side flow control of a TFTP and/or multicast TFTP session. In response to being invoked, the multicast download handler may determine whether the corresponding request is a duplicated request, 500. If the request is a duplicate request, the multicast download handler may return a previously sent acknowledge message to the requesting client device, 505. The acknowledge message may cause the requesting client device to operate as a passive client in the multicast download session.

[0019] If the request is not a duplicate, 500, the multicast download request handler may determine whether another multicast group is downloading the requested file, 510. If the requested file is being downloaded, the multicast download handler causes the requesting client to become a passive client in the existing multicast download group, 515.

[0020] If the requested file is not being downloaded by another multicast group, 510, the multicast download handler may determine whether the host server has satisfactory resources available to process the request, 520. If the server does not have satisfactory resources available, the multicast download handler may cause an error packet to be sent to the requesting client device, 530. If the server does have satisfactory resources available, the multicast download handler may save session information that may be used, for example, by other request handlers, and the multicast download request handler may create a thread to service the request, 540. Server side flow control techniques that may be used in servicing the unicast download request are described in greater detail below.

[0021] In one embodiment, to save session information, an application running on the server may maintain three linked lists (or other suitable data structures) to save information related to upload sessions, unicast download sessions and multicast download sessions. A request handler may then traverse one or more of the linked lists to determine whether the current request is a duplicate request and/or if the file is being downloaded. This may allow the server to combine download sessions where appropriate.

[0022] In one embodiment, one or more request handlers monitor host system resources to determine whether sufficient resources are available to process a request. The resources may include, for example, network bandwidth, host computing capacity, memory usage, number of active threads, etc. The resource criterion may be different for different request handlers. As an example, if the

block size of a request is L and the bandwidth of the server connection is B, then a new request may be required to satisfy

$$\sum (L/B) \leq 1/2,$$

which would allow each active session to send at least one packet every half second. Other criterion may also be used.

[0023] In one embodiment, the server may monitor packet loss rate and adjust the packet transmission rate based, at least in part, on the packet loss rate. For example, a transmission delay may be computer according to:

```

If (packet is lost){
    If(send delay is zero){
        Set send delay to 1
    } else if(send delay > timeout/4){
        Set send delay to timeout/4
    }
    Double send delay
} else {
    decrease send delay by 1 every 10 successfully received packets
until 0
}

```

Other delay computations may also be used.

[0024] In one embodiment, the techniques of Figures 2-5 can be implemented as instructions executed by an electronic system. The instructions may be stored by the electronic device or the instructions can be received by the electronic device (e.g., via a network connection). **Figure 6** is a block diagram of one embodiment of an electronic system. The electronic system illustrated in Figure 6 is intended to represent a range of electronic systems, for example, computer systems, network access devices, etc. Alternative systems, whether electronic or

non-electronic, can include more, fewer and/or different components. The electronic system of Figure 6 may represent a server device as well as the one or more client devices.

[0025] Electronic system 600 includes bus 605 or other communication device to communicate information, and processor 610 coupled to bus 605 to process information. While electronic system 600 is illustrated with a single processor, electronic system 600 can include multiple processors and/or co-processors. Electronic system 600 further includes random access memory (RAM) or other dynamic storage device 620 (referred to as memory), coupled to bus 605 to store information and instructions to be executed by processor 610. Memory 620 also can be used to store temporary variables or other intermediate information during execution of instructions by processor 610.

[0026] Electronic system 600 also includes read only memory (ROM) and/or other static storage device 630 coupled to bus 605 to store static information and instructions for processor 610. In one embodiment, static storage device 630 may include an embedded firmware agent that may have an interface compliant with an Extensible Firmware Interface (EFI) as defined by the EFI Specifications, version 1.10, published November 26, 2003, available from Intel Corporation of Santa Clara, California. In alternate embodiments, other firmware components can also be used.

[0027] Data storage device 640 is coupled to bus 605 to store information and instructions. Data storage device 640 such as a magnetic disk or optical disc and corresponding drive can be coupled to electronic system 600.

[0028] Electronic system 600 can also be coupled via bus 605 to display device 650, such as a cathode ray tube (CRT) or liquid crystal display (LCD), to display information to a user. Alphanumeric input device 660, including alphanumeric and other keys, is typically coupled to bus 605 to communicate information and command selections to processor 610. Another type of user input device is cursor control 670, such as a mouse, a trackball, or cursor direction keys to communicate direction information and command selections to processor 610 and to control cursor movement on display 650. Electronic system 600 further includes network interface 680 to provide access to a network, such as a local area network. Network interface 680 may further include one or more antennae 685 to provide a wireless network interface according to any protocol known in the art.

[0029] Instructions are provided to memory from a storage device, such as magnetic disk, a read-only memory (ROM) integrated circuit, CD-ROM, DVD, via a remote connection (e.g., over a network via network interface 680) that is either wired or wireless providing access to one or more electronically-accessible media, etc. In alternative embodiments, hard-wired circuitry can be used in place of or in combination with software instructions. Thus, execution of sequences of

instructions is not limited to any specific combination of hardware circuitry and software instructions.

[0030] An electronically-accessible medium includes any mechanism that provides (i.e., stores and/or transmits) content (e.g., computer executable instructions) in a form readable by an electronic device (e.g., a computer, a personal digital assistant, a cellular telephone). For example, a machine-accessible medium includes read only memory (ROM); random access memory (RAM); magnetic disk storage media; optical storage media; flash memory devices; electrical, optical, acoustical or other form of propagated signals (e.g., carrier waves, infrared signals, digital signals); etc.

[0031] Reference in the specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the invention. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

[0032] While the invention has been described in terms of several embodiments, those skilled in the art will recognize that the invention is not limited to the embodiments described, but can be practiced with modification and alteration within the spirit and scope of the appended claims. The description is thus to be regarded as illustrative instead of limiting.

CLAIMS

What is claimed is:

1. A method comprising:
receiving a request from a first client device to multicast a file as a plurality of packets of data from a server device to multiple client devices;
transmitting the plurality of packets of data from a server to the multiple client devices using a multicast trivial file transfer protocol (TFTP); and
applying, by the server, one or more flow control techniques not defined by the multicast TFTP.
2. The method of claim 1 wherein applying, by the server, one or more flow control techniques not defined by multicast TFTP comprises delaying a start of the transmission of the plurality of packets.
3. The method of claim 1 wherein applying, by the server, one or more flow control techniques not defined by multicast TFTP comprises:
determining whether a request to download the file is a subject of an existing multicast download session; and
causing the multiple client devices to join an existing multicast group corresponding to the existing multicast download session.

4. The method of claim 1 wherein applying, by the server, one or more flow control techniques not defined by multicast TFTP comprises modifying quality of service based, at least in part, on resource conditions.

5. The method of claim 4 wherein modifying the quality of service comprises one or more of: modifying block size and modifying timeout length.

6. The method of claim 1 wherein applying, by the server, one or more flow control techniques not defined by multicast TFTP comprises reducing a packet transmission rate.

7. The method of claim 1 wherein applying, by the server, one or more flow control techniques not defined by multicast TFTP comprises retransmitting a most recently transmitted packet in response to receiving an unexpected packet.

8. A server device comprising:
a network interface to receive messages from one or more client devices including requests to download a file stored by the server device;
a memory coupled with the network interface to store the file; and
a processor coupled with the memory and the network interface to receive a request from a first client device of the one or more client devices to multicast

the file as a plurality of packets of data from the server device to the one or more client devices, transmit the plurality of packets of data from a server to the one or more client devices using a multicast trivial file transfer protocol (TFTP), and apply one or more flow control techniques not defined by the multicast TFTP.

9. The server of claim 8 wherein the one or more flow control techniques not defined by multicast TFTP comprises delaying a start of the transmission of the plurality of packets.

10. The server of claim 8 wherein the one or more flow control techniques not defined by multicast TFTP comprises determining whether a request to download the file is a subject of an existing multicast download session, and causing the multiple client devices to join an existing multicast group corresponding to the existing multicast download session.

11. The server of claim 8 wherein the one or more flow control techniques not defined by multicast TFTP comprises modifying quality of service based, at least in part, on resource conditions.

12. The server of claim 11 wherein modifying the quality of service comprises one or more of: modifying block size and modifying timeout length.

13. The server of claim 8 wherein the one or more flow control techniques not defined by multicast TFTP comprises reducing a packet transmission rate.

14. A computer-readable medium having stored thereon instructions that, when executed by one or more processors, cause the one or more processors to:

receive a request from a first client device to multicast a file as a plurality of packets of data from a server device to multiple client devices;

transmit the plurality of packets of data from a server to the multiple client devices using a multicast trivial file transfer protocol (TFTP); and

apply, by the server, one or more flow control techniques not defined by the multicast TFTP.

15. The medium of claim 14 wherein the instructions that cause the one or more processors to apply, by the server, one or more flow control techniques not defined by multicast TFTP comprise instructions that, when executed, cause the one or more processors to delay a start of the transmission of the plurality of packets.

16. The medium of claim 14 wherein the instructions that cause the one or more processors to apply, by the server, one or more flow control

techniques not defined by multicast TFTP comprise instructions that, when executed, cause the one or more processors to:

determine whether a request to download the file is a subject of an existing multicast download session; and

cause the multiple client devices to join an existing multicast group corresponding to the existing multicast download session.

17. The medium of claim 14 wherein the instructions that cause the one or more processors to apply, by the server, one or more flow control techniques not defined by multicast TFTP comprise instructions that, when executed, cause the one or more processors to modify quality of service based, at least in part, on resource conditions.

18. The medium of claim 14 wherein the instructions that cause the one or more processors to apply, by the server, one or more flow control techniques not defined by multicast TFTP comprise instructions that, when executed, cause the one or more processors to reduce a packet transmission rate.

19. A system comprising:

one or more processors;

a network interface coupled with the one or more processors; and


a storage medium coupled with the one or more processors having stored thereon instructions that, when executed, cause the one or more processors to receive a request from a first client device to multicast a file as a plurality of packets of data to multiple client devices, transmit the plurality of packets of data using a multicast trivial file transfer protocol (TFTP), and apply one or more flow control techniques not defined by the multicast TFTP.

20. The system of claim 19 wherein the instructions that cause the one or more processors to apply one or more flow control techniques not defined by multicast TFTP comprise instructions that, when executed, cause the one or more processors to delay a start of the transmission of the plurality of packets.


21. The medium of claim 19 wherein the instructions that cause the one or more processors to apply one or more flow control techniques not defined by multicast TFTP comprise instructions that, when executed, cause the one or more processors to modify quality of service based, at least in part, on resource conditions.

22. The medium of claim 19 wherein the instructions that cause the one or more processors to apply one or more flow control techniques not defined by multicast TFTP comprise instructions that, when executed, cause the one or more processors to reduce a packet transmission rate.


1/6

**Fig. 1**


2/6

**Fig. 2**


3/6

**Fig. 3**

4/6

**Fig. 4**

5/6

**Fig. 5**

600 ↗




Fig. 6

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2005/000263

A. CLASSIFICATION OF SUBJECT MATTER

IPC⁷ H04L29/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC⁷ H04L H04L12 H04L29 H04L29/06 G06F15/16

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

CNPAT

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, EPODOC, PAJ, CNPAT: trivial file transfer protocol TFTP multicast+ server client? Multiple flow control+

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A1,2002083156 (WYSOCZYNSKI J P) 27.Jun 2002(27.06.2002)see the whole document	1-22
A	EP,A2,1248436 (PACE MICRO TECHNOLOGY PLC & MCLEOD S) 09.Oct 2002 (09.10.2002) see the whole document	1-22

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

“A” document defining the general state of the art which is not considered to be of particular relevance

“E” earlier application or patent but published on or after the international filing date

“L” document which may throw doubts on priority claim (S) or which is cited to establish the publication date of another citation or other special reason (as specified)

“O” document referring to an oral disclosure, use, exhibition or other means

“P” document published prior to the international filing date but later than the priority date claimed

“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art


“&”document member of the same patent family

Date of the actual completion of the international search
13.Oct.2005(13.10.2005)

Date of mailing of the international search report
10 • NOV 2005 C 0 11 • 2005

Name and mailing address of the ISA/CN
The State Intellectual Property Office, the P.R.China
6 Xitucheng Rd., Jimen Bridge, Haidian District, Beijing, China
100088
Facsimile No. 86-10-62019451

Authorized officer



Telephone No. 86-10-62084594

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/CN2005/000263

Patent Documents referred in the Report	Publication Date	Patent Family	Publication Date
US2002083156A1	27.06.2002	NONE	
EP1248436A2	09.10.2002	US2002178288A1	28.11.2002